

Technical Data Sheet

www.ockwells.com



Ockwells Anti-Slip Tape

Product Description

Heavy duty anti-slip tape reduces the risk of slips on potentially slippery surfaces and is manufactured with a release liner for easy application. Easy to tear by hand and holds well onto many clean and dry surfaces. Suitable for both indoor and outdoor applications, Primer highly recommended for porous surfaces.

Applications

This coarser material is ideal for industrial applications such as slippery ground surfaces i.e corridor, workshops, warehouses, slopes, stairs, tread board and machines. The abrasive coating might not be suitable for more conventional applications.

Features & Benefits

Safe and anti-skid surface, firm and durable, good chemical resistance and easy to install.

Technical Performance

Description	Units	Value
Adhesive		Solvent Rubber
Grit	grit	36
Lowest Temperature	°c	4
Highest App Temperature	°c	79

Performance

DIN 51130 (Inclined Platform Test for Slip Resistance In Shod Conditions) Results, UKAS Accreditation			
Average of Six Shod Results (Corrected): >35.0 °	Coarse non-slip tape	Category: R13	
	Standard non-slip tape	Category: R13	

Declaration of Conformity Information

Tested to DIN 51130 with UKAS Accreditation.

REACH SVHC Status

No SHVC present according to candidates list of 16th Jan 2020

RoHS Compliance Status – Not Applicable

Storage Details

Shelf life 3 years.

Recommended to store in the sealed cartons, temperature between 15°c and 30°c, humidity between 50% - 60%. Due to the different properties and characteristics of material surfaces, the purchaser and or user should test the suitability of the tape in an unexposed area in order to satisfy themselves that the tape is suitable for their requirements.

If unsure of the products suitability - DO NOT USE!

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product.

Ockwells also holds the right to change specification data without prior notice

NEWBURY

WARRINGTON

GLASGOW

EAST LONDON

01635 876336 sales@ockwells.co.uk 01925 820003 sales.warrington@ockwells.co.uk 0141 427 3366 sales.glasgow@ockwells.co.uk 020 7473 8770

sales.eastlondon@ockwells.co.uk