

# Ockwells Self Adhesive TS63 Flame Retardant Carpet Protection Film

## Description

Ockwells Self Adhesive TS63 FR Carpet Protection Film has been developed to protect carpets in commercial and public buildings under construction and refurbishment.

This protection is manufactured from high quality polythene film and has been tested to provide high levels of grip in dry conditions.

The film has a special low tack adhesive back which holds the film in place to protect carpets on a temporary basis for up to 4 weeks without leaving a residue.

Because there are many variations in carpet fibres, installation methods and site conditions, the purchaser and or user should test the suitability of Ockwells Self Adhesive TS63 FR Carpet Protection Film in an unexposed area. Leave Ockwells Self Adhesive FR Carpet Protection Film down 24 – 48 hours inspecting for adhesion and appearance.

## Ockwells Self Adhesive TS63 FR Carpet Protection Film is a certified product

Ockwells Self Adhesive TS63 FR Carpet Protection Film has shown a fire performance which ensures that, when the temporary protective covering is used on floors during building construction or refurbishment, it complies with the stringent guidelines of Warrington Certifire Certification.

- Technical Specification - TS63 Approved Product
- Warrington Certifire Certification - Cert. No. CF 747
- Factory Production and controls certified under ISO 9001:2015
- Wheelmark Certification – MED0330

## Where to use/not to use:

- Carpet Protection Film is for carpeted surfaces only
- Recommended for use on synthetic, short pile carpets only
- Also suitable for use on some short pile wool carpets – test on unexposed area to determine suitability prior to use
- Not recommended for use on any long pile or looped carpets
- Not recommended for use on oriental, antique, nylon, velour or silk carpets
- Not recommended for use when underfloor heating is in use

## Notable points:

- Cover entire carpet, do not use as a runner
- All carpets to be protected with carpet protection film should be clean and free from dust, dirt and excessive loose fibres
- Do not apply to wet or damp carpets
- Newly installed carpet fixed with adhesive should be allowed to ventilate for at least 24 hours

### Maintenance when in use:

- If carpet protection film is to be exposed to temperatures over 35°C or direct sunlight, the product should be inspected every 3 days and replaced as necessary
- In extremely heavy traffic conditions, the carpet film should be inspected every 3 days and replaced as necessary
- Carpet protection film should be replaced after 4 weeks

### Application Instructions:

- Test suitability of the carpet protection film in an unexposed area
- All loose rugs and doormats should be removed from carpeted areas prior to carpet protection film being applied
- Where smooth nosing's or carpet plates are used, they should first be lined with Ockwells Easi-Peel (Easy Tear) Tape before covering with carpet film
- Remove protective wrapping, locate start of the film
- Unwind approx. 300mm of the carpet protection film and place on the carpet adhesive side down
- Apply slight pressure over top of film whilst unwinding in the direction you wish to apply
- Roll out to desired length and cut with a safety knife

**Version Date: May 2026**

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

**NEWBURY**

**01635 876336**

[sales@ockwells.com](mailto:sales@ockwells.com)

**WARRINGTON**

**01925 820003**

[sales.warrington@ockwells.co.uk](mailto:sales.warrington@ockwells.co.uk)

**GLASGOW**

**0141 427 3366**

[sales.glasgow@ockwells.co.uk](mailto:sales.glasgow@ockwells.co.uk)

**EAST LONDON**

**020 7473 8770**

[sales.eastlondon@ockwells.co.uk](mailto:sales.eastlondon@ockwells.co.uk)