



## Ockwells Self Adhesive Carpet Protection Film

### Description

Ockwells Self Adhesive Standard Carpet Protection Film is manufactured from a tough non-flame-retardant polythene film.

The product is coated with a special low tack adhesive back designed to protect carpets on a temporary basis without creating a trip hazard.

Ockwells Self Adhesive Standard Carpet Protection Film should only be used to protect carpet for up to 4 weeks. Before using the product, the purchaser and or user must determine the suitability of the product for its intended use.

The purchaser and or user will assume all risk and liability in connection with this product.

Because there are many variations in carpet fibres, installation methods and site conditions, the purchaser and or user should test the suitability of Ockwells Self Adhesive Standard Carpet Protection Film in an unexposed area. Leave Ockwells Self Adhesive Standard Carpet Protection Film down 24 – 48 hours inspecting for adhesion and appearance.

### Where to use/not to use:

- Carpet Protection Film is for carpeted surfaces only
- Recommended for use on synthetic, short pile carpets only
- Also suitable for use on some short pile wool carpets – test on unexposed area to determine suitability prior to use
- Not recommended for use on any long pile or looped carpets
- Not recommended for use on oriental, antique, nylon, velour or silk carpets
- Not recommended for use when underfloor heating is in use

### Notable points:

- Cover entire carpet, do not use as a runner
- All carpets to be protected with carpet protection film should be clean and free from dust, dirt and excessive loose fibres
- Do not apply to wet or damp carpets
- Newly installed carpet fixed with adhesive should be allowed to ventilate for at least 24 hours

### Maintenance when in use:

- If carpet protection film is to be exposed to temperatures over 35°C or direct sunlight, the product should be inspected every 3 days and replaced as necessary
- In extremely heavy traffic conditions, the carpet film should be inspected every 3 days and replaced as necessary
- Carpet protection film should be replaced after 4 weeks

### Application Instructions:

- Test suitability of the carpet protection film in an unexposed area
- All loose rugs and doormats should be removed from carpeted areas prior to carpet protection film being applied
- Where smooth nosing's or carpet plates are used, they should first be lined with Ockwells Easi-Peel (Easy Tear) Tape before covering with carpet film
- Remove protective wrapping, locate start of the film
- Unwind approx. 300mm of the carpet protection film and place on the carpet adhesive side down
- Apply slight pressure over top of film whilst unwinding in the direction you wish to apply
- Roll out to desired length and cut with a safety knife

Issued: 19/05/2026

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

#### NEWBURY

01635 876336  
sales@ockwells.co.uk

#### WARRINGTON

01925 820003  
sales.warrington@ockwells.co.uk

#### GLASGOW

0141 427 3366  
sales.glasgow@ockwells.co.uk

#### EAST LONDON

020 7473 8770  
sales.eastlondon@ockwells.co.uk