

Technical Data Sheet

www.ockwells.com



Ockwells Door Sleeves

- Protection against scratches, dust, dirt, paint etc
- Helps reduce the potential costs of damage

Description

Ockwells Door Sleeves is a 30% Post-Consumer Waste Recycled film, designed to protect doors during the refurbishment process. Ockwells Door Sleeves can be simply and quickly applied to universal door fittings, and can be held in place with jointing tape, providing a waterproof barrier to suit a range of demanding environments. Ockwells Door Sleeves are designed to provide high quality protection against scratches, dust, dirt, paint and mortar splashes. The Door Sleeves can also reduce costly damage to pre-finished doors during the refurbishment process. Ockwells Door Sleeves are supplied on a roll containing 20 bags per reel (POR - Perforated on a Reel). Each sleeve is 915mm x 2200mm allowing the sleeve to be fitted to most metric and imperial doors with ease.

Installation

Ockwells Door Sleeves can be fitted to most metric and imperial doors with ease. Simply tear off a sleeve from the roll at the perforation mark, and using the open end, pull the sleeve over the door. At the hinge door end, thread one side of the film through and overlap the sleeve by at least 150mm; then seal the lap with jointing tape. Any surplus film can be folded over the top of the door and should be secured with jointing tape to ensure a snug fit. This will allow the door to remain in operation whilst preventing cosmetic damage.

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product.

Ockwells also holds the right to change specification data without prior notice

NEWBURY

WARRINGTON

GLASGOW

EAST LONDON