



Ockwells Hazard Warning PVC Tape

Description

Manufactured from a plasticised polyvinyl chloride film and coated with an aggressive pressure sensitive rubber-based adhesive.

Applications

- Hazard Tape should be used to highlight hazards in and around construction sites
- Used on scaffolding poles and as a warning tape around trenches etc

Properties	Unit	Value
Total thickness	µm	150 ± 10
Adhesive	-	Rubber
Elongation	%	85
Initial Tack (Ball Test)	Ball no	≥ 10
180° Peel Adhesion	N/IN	≥ 2.5
Tensile Strength	N/IN	≥ 35
Service temperature	°C	0 ~ +80
Storage temperature	°C	Normal room temp.
Shelf life	Month	24

Unless otherwise indicated the figures above are average values and should not be treated at face value for specification purposes.

Application surface should be clean, dry and free of grease, oil, moisture, dirt, and other conditions.

Due to the different properties and characteristics of material surfaces, the purchaser and or user should test the suitability of the tape in an unexposed area to satisfy themselves that the tape is suitable for their requirements.

If unsure of the products suitability - DO NOT USE!

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

NEWBURY

01635 876336
sales@ockwells.co.uk

WARRINGTON

01925 820003
sales.warrington@ockwells.co.uk

GLASGOW

0141 427 3366
sales.glasgow@ockwells.co.uk

EAST LONDON

020 7473 8770
sales.eastlondon@ockwells.co.uk