



LINEMARKER PAINT – All Colours

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Linemarker Paint - All Colours

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PC9a Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Supplier Aerosol Solutions Ltd

Unit C2 Bridgefield Ind Est

Draycott Road

Breaston, Derby

DE72 3DS

T 01332 870030 F 01332 870033

sales@aerosolsolutions.co.uk

1.4. Emergency telephone number

Emergency telephone 01332 870 030 (Monday to Friday – 8:30am – 5:00pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 3 - H412

Human health Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Environmental The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See Section 12 for additional information on ecological hazards.

Physicochemical Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Hazard pictograms



Signal word



Danger

Hazard statements

H222 Extremely flammable aerosol.

H319 Causes serious eye irritation.

H229 Pressurised container: may burst if heated.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

| | |
|---------------------------------|---|
| Precautionary statements | <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P102 Keep out of reach of children.</p> <p>P501 Dispose of contents/ container in accordance with local regulations.</p> <p>P314 Get medical advice/ attention if you feel unwell.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P262 Do not get in eyes, on skin, or on clothing.</p> |
|---------------------------------|---|

Supplemental label Information EUH066 Repeated exposure may cause skin dryness or cracking.

Contains ACETONE, AROMATIC HYDROCARBON, BUTYL ACETATE -norm

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | | | |
|---|----------------------|--|---------------|
| PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS | | | 30-60% |
| CAS number: 68476-85-7 | EC number: 270-704-2 | | |
| Classification Flam. Gas 1 - H220 Press. Gas (Liq.) - H280 | | | |

| | | | |
|---|----------------------|---|---------------|
| ACETONE | | | 10-30% |
| CAS number: 67-64-1 | EC number: 200-662-2 | REACH registration number: 01-2119471330-49 | |
| Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336 | | | |

| | | | |
|--|----------------------|---|--------------|
| SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA | | | 5-10% |
| CAS number: 64742-95-6 | EC number: 265-199-0 | REACH registration number: 01-2119455851-35 | |
| Classification Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411 | | | |

| | | | |
|---|----------------------|---|---------------|
| BUTYL ACETATE -norm | | | 1-5% |
| CAS number: 123-86-4 | EC number: 204-658-1 | REACH registration number: 01-2119485493-29 | |
| Classification Flam. Liq. 3 - H226 STOT SE 3 - H336 | | | |
| 1,2,4-TRIMETHYLBENZENE | | | 1-5% |
| CAS number: 95-63-6 | EC number: 202-436-9 | | |
| Classification Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Aquatic Chronic 2 - H411 | | | |
| CUMENE | | | <1% |
| CAS number: 98-82-8 | EC number: 202-704-5 | | |
| Classification Flam. Liq. 3 - H226 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411 | | | |
| MESITYLENE | | | <1% |
| CAS number: 108-67-8 | EC number: 203-604-4 | | |
| Classification Flam. Liq. 3 - H226 STOT SE 3 - H335 Aquatic Chronic 2 - H411 | | | |

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------|--|
| General information | Move affected person to fresh air at once. |
| Inhalation | If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately. |
| Ingestion | Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention. |
| Skin contact | Remove contaminated clothing immediately and wash skin with soap and water. |
| Eye contact | Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|---------------------|---|
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
|---------------------|---|

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|----------------------|------------------------|
| Notes for the doctor | Treat symptomatically. |
|----------------------|------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

| | |
|------------------|--|
| Specific hazards | Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Forms explosive mixtures with air. The product is extremely flammable. |
|------------------|--|

5.3. Advice for firefighters

| | |
|--|--|
| Protective actions during firefighting | Cool containers exposed to heat with water spray and remove them from the fire area can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved. |
|--|--|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|----------------------|---|
| Personal precautions | Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours. |
|----------------------|---|

6.2. Environmental precautions

| | |
|---------------------------|---|
| Environmental precautions | Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable non-combustible material. |
|---------------------------|---|

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|--|
| Methods for cleaning up | Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb spillage with non-combustible, absorbent material. |
|-------------------------|--|

6.4. Reference to other sections

| | |
|-----------------------------|---|
| Reference to other sections | For personal protection, see Section 8. For waste disposal, see Section 13. |
|-----------------------------|---|

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-------------------|--|
| Usage precautions | Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Do not spray on a naked flame or any incandescent material. Eliminate all sources of ignition. |
|-------------------|--|

7.2. Conditions for safe storage, including any incompatibilities

| | |
|---------------------|--|
| Storage precautions | Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. |
|---------------------|--|

7.3. Specific end use(s)

| | |
|---------------------|---|
| Specific end use(s) | The identified uses for this product are detailed in Section 1.2. |
|---------------------|---|

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA

Long-term exposure limit (8-hour TWA): SUP 600 mg/m³

Long-term exposure limit (8-hour TWA): WEL 50 ppm

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

1,2,4-TRIMETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 25 ppm

CUMENE

Long-term exposure limit (8-hour TWA): WEL 25 ppm 125 mg/m³

Short-term exposure limit (15-minute): WEL 50 ppm 250 mg/m³

Sk

MESITYLENE

Long-term exposure limit (8-hour TWA): WEL 25 ppm

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

| | |
|---------------------|---|
| Ingredient comments | WEL = Workplace Exposure Limits WEL = Workplace Exposure Limits |
|---------------------|---|

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA (CAS: 64742-95-6)

| | |
|------|---|
| DNEL | Industry, Workers - Inhalation; Long term systemic effects: 150 mg/m ³ |
|------|---|

| | |
|------------|--|
| Consumer - | Inhalation; Long term systemic effects: 32 mg/m ³ |
|------------|--|

BUTYL ACETATE -norm (CAS: 123-86-4)

| | |
|------|---|
| DNEL | Workers - Inhalation; Short term systemic effects: 960 mg/m ³ |
| | Workers - Inhalation; Short term local effects: 960 mg/m ³ |
| | Workers - Inhalation; Long term systemic effects: 480 mg/m ³ |
| | Workers - Inhalation; Long term local effects: 480 mg/m ³ |
| | General population - Inhalation; Short term systemic effects: 859.7 mg/m ³ |
| | General population - Inhalation; Short term local effects: 859.7 mg/m ³ |
| | Workers - Inhalation; Long term systemic effects: 102.34 mg/m ³ |
| | General population - Inhalation; Long term local effects: 102.34 mg/m ³ |

| | |
|------|---|
| PNEC | <ul style="list-style-type: none"> - Fresh water; 0.18 mg/l - marine water; 0.18 mg/l - Intermittent release; 0.36 mg/l - STP; 35.6 mg/l - Sediment (Freshwater); 0.981 mg/kg - Sediment (Marinewater); 0.0981 mg/l - Soil; 0.0903 mg/kg |
|------|---|

8.2. Exposure controls

Protective equipment



| | |
|----------------------------------|---|
| Appropriate engineering controls | Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients |
| Personal protection | When using do not smoke. |
| Eye/face protection | Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. |
| Hand protection | Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacture, who can provide information about the breakthrough time of the glove material. |
| Hygiene measures | Wash hands after handling. Wash promptly if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin. |
| Respiratory protection | If ventilation is inadequate, suitable respiratory protection must be worn. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| Appearance | Aerosol. |
| Colour | Various colours. |
| Odour | Organic solvents. |
| Flash point | < -40°C |
| Upper/lower flammability or explosive limits | Lower flammable/explosive limit: 1.8% Upper flammable/explosive limit: 9.5% |
| Auto-ignition temperature | 410-580°C |
| Comments | Information given is applicable to the major ingredient. |

9.2. Other information

| | |
|---------------------------|---|
| Other information | Not available. |
| Volatile organic compound | This product contains a maximum VOC content of 668 g/l. |

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|------------|---|
| Reactivity | Stable at normal ambient temperatures and when used as recommended. |
|------------|---|

10.2. Chemical stability

| | |
|-----------|---|
| Stability | Avoid the following conditions: Heat, sparks, flames. |
|-----------|---|

10.3. Possibility of hazardous reactions

| | |
|------------------------------------|---|
| Possibility of hazardous Reactions | Does not decompose when used and stored as recommended. |
|------------------------------------|---|

10.4. Conditions to avoid

| | |
|---------------------|--|
| Conditions to avoid | Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight. |
|---------------------|--|

10.5. Incompatible materials

| | |
|--------------------|--|
| Materials to avoid | Keep away from oxidising materials, heat and flames. |
|--------------------|--|

10.6. Hazardous decomposition products

| | |
|----------------------------------|--|
| Hazardous decomposition products | Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours. |
|----------------------------------|--|

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|----------------------------------|--|
| General information | Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal. |
| Inhalation | In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death. |
| Skin contact | Repeated exposure may cause skin dryness or cracking. |
| Eye contact | Irritating to eyes. Vapour or spray in the eyes may cause irritation and smarting. Repeated exposure may cause chronic eye irritation. |
| Acute and chronic health Hazards | Arrhythmia (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. |
| Route of exposure | Inhalation |
| Target organs | Central nervous system Respiratory system, lungs |
| Medical symptoms | Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness. Skin irritation. |

SECTION 12: Ecological information

| | |
|-------------|--|
| Ecotoxicity | ENVIRONMENTAL HAZARDS: This product has not been tested but contains ingredients which are harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses. |
|-------------|--|

12.1. Toxicity

| | |
|----------|----------------|
| Toxicity | Not available. |
|----------|----------------|

12.2. Persistence and degradability

| | |
|-------------------------------|----------------|
| Persistence and degradability | Not available. |
|-------------------------------|----------------|

12.3. Bioaccumulative potential

| | |
|---------------------------|----------------|
| Bioaccumulative potential | Not available. |
|---------------------------|----------------|

12.4. Mobility in soil

| | |
|----------|------------|
| Mobility | Not known. |
|----------|------------|

12.5. Results of PBT and vPvB assessment

| | |
|------------------------------------|----------------|
| Results of PBT and vPvB assessment | Not available. |
|------------------------------------|----------------|

12.6. Other adverse effects

| | |
|-----------------------|----------------|
| Other adverse effects | Not available. |
|-----------------------|----------------|

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|---------------------|---|
| General information | Do not puncture or incinerate, even when empty. |
|---------------------|---|

| | |
|------------------|---|
| Disposal methods | Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion. |
|------------------|---|

SECTION 14: Transport information

14.1. UN number

| | |
|------------------|------|
| UN No. (ADR/RID) | 1950 |
| UN No. (IMDG) | 1950 |
| UN No. (ICAO) | 1950 |
| UN No. (ADN) | 1950 |

14.2. UN proper shipping name

| | |
|--------------------------------|----------|
| Proper shipping name (ADR/RID) | AEROSOLS |
|--------------------------------|----------|

| | |
|-----------------------------|----------|
| Proper shipping name (IMDG) | AEROSOLS |
| Proper shipping name (ICAO) | AEROSOLS |
| Proper shipping name (ADN) | AEROSOLS |

14.3. Transport hazard class(es)

| | |
|-----------------------------|-----|
| ADR/RID class | 2.1 |
| ADR/RID classification code | 5F |
| ADR/RID label | 2.1 |
| IMDG class | 2.1 |
| ICAO class/division | 2.1 |
| ADN class | 2.1 |

Transport labels



14.4. Packing group

| | |
|-----------------------|------|
| ADR/RID packing group | None |
| IMDG packing group | None |
| ICAO packing group | None |
| ADN packing group | None |

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

| | |
|-------------------------|----------|
| EmS | F-D, S-U |
| ADR transport category | 2 |
| Tunnel restriction code | (D) |

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|----------------------|---|
| National regulations | The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824). EH40/2005 Workplace exposure limits. The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. |
| EU legislation | Commission Regulation (EU) No 453/2010 of 20 May 2010. |
| Guidance | Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999 |

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

| | |
|---------------------------|--|
| Revision comments | Supplemental information added. |
| Revision date | 25/01/2019 |
| Revision | 3 |
| SDS number | 20831 |
| SDS status | Approved. |
| Hazard statements in full | H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

NEWBURY

01635 876336
sales@ockwells.co.uk

WARRINGTON

01925 820003
sales.warrington@ockwells.co.uk

GLASGOW

0141 427 3366
sales.glasgow@ockwells.co.uk

EAST LONDON

020 7473 8770
sales.eastlondon@ockwells.co.uk