


### Scaffold Sheeting FR – CF5662 & CF5663

Reinforced polyolefin sheeting system for temporary containment and weather protection applications. Powerclad reinforcement bands incorporate eyelets every 10cm to provide a versatile system for all tube & fitting and modular scaffold systems and the ability to vary the support density according to anticipated wind forces.

PRODUCT	Flame retardant 	Colour	Weight EN 695 gsm	Tensile strength BS 7955 N/50mm	Eyelet strength BS 7955 Newtons	Conforms to	Temperature range °C	Aerodynamic coefficient EN ISO 9237 Cf	Sizes metres	Roll weight kg	Pallet quantity
FLAME RETARDANT SHEETING											
Powerclad FR Premium	LPS1215 Cert No. 965b/01 and No. 1351b/01* LPS 1207 Cert No. 965a/01 and No. 1351a/01* OR TS 62 Cert No. CF5662 and TS 63 Cert. No. CF5663 BS 476 Part 12C; B-s1,d0 EN 13501-1	Ivory	240	MD 800 XD 750	900	BS 7955	-40 to +70	1.0	2.0 x 45	22	39
									2.2 x 40	22	39
									2.7 x 20	13	39
									3.0 x 45	33	23
									4.0 x 45	44	17
Powerclad FR Standard	LPS 1215 Cert. No. 965b/04 and No. 1351b/02* LPS 1207 Cert. No. 965a/02 and No. 1351a/02* OR TS 62 Cert No. CF5662 and TS 63 Cert. No. CF5663 BS 476 Part 12C; B-s1,d0 EN 13501-1	Ivory	170	MD >630 XD >630	>500	BS 7955	-40 to +70	1.0	2.0 x 45	15.8	39
									2.2 x 40	15.5	39
									3.0 x 45	23.5	23
									3.2 x 36	20.0	33
									4.0 x 36	25.5	33

**Fastening ties:** Elasticated Toggle Ties BS 7955 Pass break strength 500 N (28cm reach)

**Flexo printing:** Maximum print area 1070 x 730mm; repeats at 1270mm; up to 2 colours; subject to minimum quantities

**Wide format digital printing:** any size, no minimum quantity.

Ockwells are a division of SIG Trading Ltd. SIG Trading Ltd terms and conditions of sale apply to all transactions. A copy can be provided on request and will be incorporated into the contract of sale.

Version Date: June 2025

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

NEWBURY

01635 876336

[sales@ockwells.com](mailto:sales@ockwells.com)

WARRINGTON

01925 820003

[sales.warrington@ockwells.co.uk](mailto:sales.warrington@ockwells.co.uk)

GLASGOW

0141 427 3366

[sales.glasgow@ockwells.co.uk](mailto:sales.glasgow@ockwells.co.uk)

EAST LONDON

020 7473 8770

[sales.eastlondon@ockwells.co.uk](mailto:sales.eastlondon@ockwells.co.uk)