

### FR Scaffold Sheet – CF6125

#### Product Description:

Certificated Flame-Retardant Scaffold Sheet certified to TS62 Standard.

#### Product Features:

Fire Resistant – Certificated TS62 – CF6125

Provides protection against the elements for personnel and materials.

UV Resistant

Helps to reduce noise levels.

#### Product Specifications:

- 2m x 45m – 170GSM Coverage 90m<sup>2</sup>
- 2.25m x 40m – 170GSM Coverage 90m<sup>2</sup>
- 3m x 45m – 170GSM Coverage 135m<sup>2</sup>

#### Performance Data:

Materials:	Co-Polymer LDPE
Weave:	10 x 10 Mesh 1670 dtex PET
Eyelet Strength:	650/N50mm
Conforms to:	BS7955-1999
Install to:	BS8410:2007

Fastening Ties: Elasticated Bullet Toggle Ties to BS7955-1999, Breaking Load 650N

*Version Date: 18/06/25*

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

#### NEWBURY

**01635 876336**

[sales@ockwells.com](mailto:sales@ockwells.com)

#### WARRINGTON

**01925 820003**

[sales.warrington@ockwells.co.uk](mailto:sales.warrington@ockwells.co.uk)

#### GLASGOW

**0141 427 3366**

[sales.glasgow@ockwells.co.uk](mailto:sales.glasgow@ockwells.co.uk)

#### EAST LONDON

**020 7473 8770**

[sales.eastlondon@ockwells.co.uk](mailto:sales.eastlondon@ockwells.co.uk)