



## Orange Low Tack Tape (UV-resistant)

### Description

Manufactured from a polythene film coated with a clean peel, dispersion acrylic adhesive.

### Applications

As well as being UV-resistant, this tape is also water resistant and frost resistant and has an adhesive that is non-corrosive, making it the ideal tape for use on construction sites.

Properties	Unit	Value
Total thickness	mm	0.11
Adhesive	-	Acrylic
Elongation	%	200
RoHS Compliant	-	Yes
Adhesion Steel	N/cm	1.3
Service temperature	°C	-40 to +60
Storage temperature	°C	+12 to +25
Application temperature	°C	0 to +40

Unless otherwise indicated the figures above are average values and should not be treated at face value for specification purposes. Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

Application surface should be clean, dry and free of grease, oil, moisture, dirt and other conditions.

Depending on the weather conditions and surface applied to, can stay in situ for up to 13 weeks.

Due to the different properties and characteristics of material surfaces, the purchaser and or user should test the suitability of the tape in an unexposed area in order to satisfy themselves that the tape is suitable for their requirements.

If unsure of the products suitability - DO NOT USE!

#### NEWBURY

Unit 6, Transigo,  
Gables Way, Thatcham,  
Berkshire RG19 4ZA

**T: 01635 876336**  
sales@ockwells.com

#### WARRINGTON

Unit 12, Cameron Court,  
Winwick Quay,  
Warrington WA2 8RE

**T: 01925 820003**  
sales.warrington@ockwells.com

#### GLASGOW

Unit 2, 45 Mackellan Street,  
Kinning Parkway Estate,  
Glasgow G41 1RR

**T: 0141 427 3366**  
sales.glasgow@ockwells.com

#### EAST LONDON

Unit E1, Thames View Business Centre  
Fairview Industrial Park  
Rainham RM13 8BT

**T: 020 7473 8770**  
sales.rainham@ockwells.com