



Ockwells Pyramat Hi-Vis Rubber Matting

Description

Ockwells Pyramat is a hi-vis, hardwearing grade of vulcanized rubber matting with high grip, multi-directional pyramid design on one side and a plain, smooth reverse. Available in hi-vis yellow with a thickness of 3mm. Ideally suited for designated walkways for foot traffic where a multi-directional anti slip mat is preferred.

- Slip resistant multi-directional pyramid surface
- Safe, Hygienic & Non Toxic
- Oil & Grease Resistant
- Visible even from high vantage points
- Water can drain in all directions
- Can be pressure washed
- Durable vulcanized rubber compound
- Rip resistant

Measured Aspect	Unit	Specification Requirement
Thickness:	mm	3
Width:	m	1
Length:	m	10
Weight:	kg/m2	3.60
Colour:		Yellow
Compound:		Vulcanized Rubber (natural & synthetic mix)
Hardness:	Shore A	70 \pm 5.00
Specific Gravity:	gm/cc	1.5
Tensile Strength:	kg/cm2	35
Elongation:	%	250
Working Temperature Range:	°C	-30 to +70
Slip Resistance tested in accordance with IEC:61111 Standard	N	Results of 52N & 57N (pass) Minimum reading for pass = 50N

NEWBURY

Unit 6, Transigo,
Gables Way, Thatcham,
Berkshire RG19 4ZA

T: 01635 876336
sales@ockwells.com

WARRINGTON

Unit 12, Cameron Court,
Winwick Quay,
Warrington WA2 8RE

T: 01925 820003
sales.warrington@ockwells.com

GLASGOW

Unit 2, 45 Mackellan Street,
Kinning Parkway Estate,
Glasgow G41 1RR

T: 0141 427 3366
sales.glasgow@ockwells.com

EAST LONDON

Unit E1, Thames View Business Centre
Fairview Industrial Park
Rainham RM13 8BT

T: 020 7473 8770
sales.rainham@ockwells.com