Technical Data Sheet

www.ockwells.com



Ockwells Standard & FR Vented Sheet

Strong, air permeable sheeting suitable for all scaffold systems and temporary perimeter fencing.

PRODUCT	Flame retartant	Colour	weight Weight	Tensile Stength	Fastening Strength Newtons	Conforms to	م range	Air permeability	Verodynamic Cefficient	s ez is	ة Roll weight	Pallet quantity
FLAME RETARDANT GRADES												
Flame Retardant Vented Sheeting	BS 476 Part 12C	White	100	MD >630 XD >630	>500	BS 7955	-40 to +70	Windbreak 89% EN ISO 9237	NT	1.8 x 45	9.5	39
NON-FLAME RETARDANT GRADE												
Vented Sheeting	NA	White	100	MD >630 XD >630	>500	BS 7955	-40 to +70	Windbreak 89% EN ISO 9237	NT	1.8 x 45	9.5	39

Fastening ties: Elasticated Toggle Ties

BS 7955 Pass break strength 500 N (28cm reach)

Flexo printing: maximum print area 1070 x 730mm; repeats at 1270mm; up to 2 colours; subject to minimum quantities **Wide format digital printing**: any size, no minimum quantity

Ockwells are a division of SIG Trading Ltd. SIG Trading Ltd terms and conditions of sale apply to all transactions. A copy can be provided on request and will be incorporated into the contract of sale.

NEWBURY	WARRINGTON	GLASGOW	EAST LONDON	
Unit 6, Transigo,	Unit 29, Melford Court,	Unit 2, 45 Maclellan Street	Unit E1, Thames View	
Gables Way, Thatcham,	Woolston, Warrington,	Kinning Parkway Estate,	Business Centre, Fairview Ind	
Berkshire RG19 4ZA	Cheshire WA1 4RZ	Glasgow G41 1RR	Park, Rainham RM13 8BT	
T: 01635 876336	T: 01925 820003	T: 0141 427 3366	T: 020 7473 8770	
sales@orkwells rom	sales warrington@ockwolls.com	sales glasgow@ockwells.com	1 11 0 1 11	