



Double Sided PVC Tape

Product Description

Double sided Blue stretchable LDPE carrier coated with clear permanent synthetic rubber-based adhesive on closed side and clear removable synthetic rubber-based adhesive on the open side, supplied with white silicone liners.

Applications

Temporary fastening, especially for non-slip mats or carpets.

Features & Benefits

Perm/Peel

Application Notes

Apply with a firm pressure to clean, non-porous surfaces. Test an inconspicuous area before use to determine suitability.

Technical Performance

Description	Units	Value	Test Method
Total thickness	mic	150	Digital calliper
180° Peel	N/cm	Open side 15 Closed side 2.7	AFERA 5004
Elongation at break	%	4	AFERA 5004
Tensile strength	N/cm	17	AFERA 5004
Static shear	hrs	Open side 300 Closed side 24	FTM 8su acciaio
Rolling ball	cm	Open side 3 Closed side 3.5	PSTC 6
Performance Temperature	°c	Min -10 max +50	-

Storage Details

Shelf life recommended 12 months from date of despatch at the moderate temperature and humidity environment.

Due to the different properties and characteristics of material surfaces, the purchaser and or user should test the suitability of the tape in an unexposed area in order to satisfy themselves that the tape is suitable for their requirements.

If unsure of the products suitability - DO NOT USE!

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

NEWBURY

01635 876336
sales@ockwells.co.uk

WARRINGTON

01925 820003
sales.warrington@ockwells.co.uk

GLASGOW

0141 427 3366
sales.glasgow@ockwells.co.uk

EAST LONDON

020 7473 8770
sales.eastlondon@ockwells.co.uk