

# POWERCLAD<sup>®</sup> SCAFFOLD SHEETING FOR TUBE & FITTING AND MODULAR SCAFFOLD SYSTEMS


PRODUCT

Revision 5.7

powerclad.com

## Ockwells Standard & FR Vented Sheet

Strong, air permeable sheeting suitable for all scaffold systems and temporary perimeter fencing.

PRODUCT	Flame retardant	Colour	Weight EN 695 gsm	Tensile strength BS 7955 N/50mm	Fastening strength BS 7955 Newtons	Conforms to	Temperature range °C	Air permeability	Aerodynamic coefficient EN ISO 9237 Cf	Sizes metres	Roll weight kg	Pallet quantity
<b>FLAME RETARDANT GRADES</b>												
Flame Retardant Vented Sheeting	 BS 476 Part 12C	White	100	MD >630 XD >630	>500	BS 7955	-40 to +70	Windbreak 89% EN ISO 9237	NT	1.8 x 45	9.5	39
<b>NON-FLAME RETARDANT GRADE</b>												
Vented Sheeting	NA	White	100	MD >630 XD >630	>500	BS 7955	-40 to +70	Windbreak 89% EN ISO 9237	NT	1.8 x 45	9.5	39

Powerclad<sup>®</sup> is a registered trademark of Industrial Textiles & Plastics Ltd. E&OE.

### NEWBURY

01635 876336  
sales@ockwells.co.uk

### WARRINGTON

01925 820003  
sales.warrington@ockwells.co.uk

### GLASGOW

0141 427 3366  
sales.glasgow@ockwells.co.uk

### EAST LONDON

020 7473 8770  
sales.eastlondon@ockwells.co.uk