



Orange Low Tack Tape (UV-resistant)

Description

Manufactured from a polythene film coated with a clean peel, dispersion acrylic adhesive.

Applications

As well as being UV-resistant, this tape is also water resistant and frost resistant and has an adhesive that is non-corrosive, making it the ideal tape for use on construction sites.

Properties	Unit	Value
Total thickness	mm	0.11
Adhesive	-	Acrylic
Elongation	%	200
RoHS Compliant	-	Yes
Adhesion Steel	N/cm	1.3
Service temperature	°C	-40 to +60
Storage temperature	°C	+12 to +25
Application temperature	°C	0 to +40

Unless otherwise indicated the figures above are average values and should not be treated at face value for specification purposes. Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

Application surface should be clean, dry and free of grease, oil, moisture, dirt and other conditions.

Depending on the weather conditions and surface applied to, can stay in situ for up to 13 weeks.

Due to the different properties and characteristics of material surfaces, the purchaser and or user should test the suitability of the tape in an unexposed area in order to satisfy themselves that the tape is suitable for their requirements.

If unsure of the products suitability - DO NOT USE!

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

NEWBURY

01635 876336
sales@ockwells.co.uk

WARRINGTON

01925 820003
sales.warrington@ockwells.co.uk

GLASGOW

0141 427 3366
sales.glasgow@ockwells.co.uk

EAST LONDON

020 7473 8770
sales.eastlondon@ockwells.co.uk