

POWERCLAD[®] DEBRIS NETTING



PRODUCT DATA

Revision 6.1

powerclad.com

POWERCLAD[®] Debris Netting is a monofilament polyethylene knitted netting for temporary containment and weather protection applications, suitable for all tube & fitting and modular scaffold systems.

Flame Retardant Grade is particularly recommended for safety-critical installations.

PRODUCT	Flame retardant	Colours	°C	ASTM D737 EN ISO 9237 cm3/cm2/sec	Cf	Meters	Pallet quantity
FLAME RETARDANT GRADE							
Powerclad DNFR Flame Retardant Debris Netting	TS 62 Cert No. CF 6049 BS 476 Part 12C EN 13501-1, B-s1,d0*	White, Green, Blue, Red, Black** Other colours available on request	-40 to +70	>1,500	0.45	2.0 x 50 3.0 x 50 3.2 x 50	50 30 30
NON-FLAME RETARDANT GRADE							
Powerclad DN Debris Netting	NA	Green, Blue, Red, Yellow, Orange, Black, Pink, White**	-40 to +70	>1,500	NT	2.0 x 50 3.0 x 50	50 30

*Tested For White **Not all colours available in all sizes.

Issue Date: November 2023

NEWBURY 01635 876336 sales@ockwells.co.uk	WARRINGTON 01925 820003 sales.warrington@ockwells.co.uk	GLASGOW 0141 427 3366 sales.glasgow@ockwells.co.uk	EAST LONDON 020 7473 8770 sales.eastlondon@ockwells.co.uk
---	---	--	---